

**TECHNICAL SPECIFICATIONS**

Filter Media	: Minipleat Micro Glass Fibre
Frame Material	: Aluminium Steel
Classification (EN1822)	: E10 - U17
Gasket	: Cont. Round Pu / Flat Epdm
Seperator	: Hotmelt
Sealant	: 2K Polyurethane
Final Pressure Drop	: 600 Pa
Max. Temperature:	: 80 °C
Max. Moisture	: 90%
Rated Face Velocity	: 0,45 m/s



PRODUCT CODE	CLASS EN1822	WIDTH (mm)	HEIGHT (mm)	DEPTH (mm)	FILTRATION AREA (m2)	NOMINAL AIR FLOW (m3/h)	INITIAL PRESSURE DROP (± 10% Pa)
HTF-10-A-203-203-69-S-DP-DG	E 10	203	203	78	1,10	75	65
HTF-10-A-305-305-69-S-DP-DG	E 10	305	305	78	2,45	150	65
HTF-10-A-305-610-69-S-DP-DG	E 10	305	610	78	4,90	300	65
HTF-10-A-457-457-69-S-DP-DG	E 10	457	457	78	5,50	340	65
HTF-10-A-535-535-69-S-DP-DG	E 10	535	535	78	7,55	465	65
HTF-10-A-575-575-69-S-DP-DG	E 10	575	575	78	8,70	535	65
HTF-10-A-610-610-69-S-DP-DG	E 10	610	610	78	9,80	600	65
HTF-10-A-610-762-69-S-DP-DG	E 10	610	762	78	12,25	750	65
HTF-10-A-610-915-69-S-DP-DG	E 10	610	915	78	14,70	900	65
HTF-10-A-610-1220-69-S-DP-DG	E 10	610	1220	78	19,60	1200	65
HTF-10-A-610-1830-69-S-DP-DG	E 10	610	1830	78	29,40	1800	65
HTF-13-A-203-203-69-S-DP-DG	H 13	203	203	78	1,10	75	100
HTF-13-A-305-305-69-S-DP-DG	H 13	305	305	78	2,45	150	100
HTF-13-A-305-610-69-S-DP-DG	H 13	305	610	78	4,90	300	100
HTF-13-A-457-457-69-S-DP-DG	H 13	457	457	78	5,50	340	100
HTF-13-A-535-535-69-S-DP-DG	H 13	535	535	78	7,55	465	100
HTF-13-A-575-575-69-S-DP-DG	H 13	575	575	78	8,70	535	100
HTF-13-A-610-610-69-S-DP-DG	H 13	610	610	78	9,80	600	100
HTF-13-A-610-762-69-S-DP-DG	H 13	610	762	78	12,25	750	100
HTF-13-A-610-915-69-S-DP-DG	H 13	610	915	78	14,70	900	100
HTF-13-A-610-1220-69-S-DP-DG	H 13	610	1220	78	19,60	1200	100
HTF-13-A-610-1830-69-S-DP-DG	H 13	610	1830	78	29,40	1800	100
HTF-14-A-203-203-69-S-DP-DG	H 14	203	203	78	1,10	75	125
HTF-14-A-305-305-69-S-DP-DG	H 14	305	305	78	2,45	150	125
HTF-14-A-305-610-69-S-DP-DG	H 14	305	610	78	4,90	300	125
HTF-14-A-457-457-69-S-DP-DG	H 14	457	457	78	5,50	340	125
HTF-14-A-535-535-69-S-DP-DG	H 14	535	535	78	7,55	465	125
HTF-14-A-575-575-69-S-DP-DG	H 14	575	575	78	8,70	535	125
HTF-14-A-610-610-69-S-DP-DG	H 14	610	610	78	9,80	600	125
HTF-14-A-610-762-69-S-DP-DG	H 14	610	762	78	12,25	750	125
HTF-14-A-610-915-69-S-DP-DG	H 14	610	915	78	14,70	900	125
HTF-14-A-610-1220-69-S-DP-DG	H 14	610	1220	78	19,60	1200	125
HTF-14-A-610-1830-69-S-DP-DG	H 14	610	1830	78	29,40	1800	125