

HEPA TERMINAL FILTERS-GEL SEAL 80 MM ALUMINIUM FRAME **TECHNICAL SPECIFICATIONS**

Filter Media	: Minipleat Micro Glass Fibre
Frame Material	: Aluminium Steel
Classification (EN1822)	: E10 - U17
Gasket	: Gel Seal
Seperator	: Hotmelt
Sealant	: 2K Polyurethane
Final Pressure Drop	: 600 Pa
Max. Temperature	: 80 °C
Max. Moisture	: 90%



Gel fluid seal guarantee
a leak free design when
assembled with a knife
edge housing

PRODUCT CODE	CLASS EN1822	WIDTH (mm)	HEIGHT (mm)	DEPTH (mm)	FILTRATION AREA (m ²)	NOMINAL AIR FLOW (m ³ /h)	INITIAL PRESSURE DROP (± 10% Pa)
HTF-13-A-203-203-80-S-DG-BG	H 13	203	203	80	1,10	75	100
HTF-13-A-305-305-80-S-DG-BG	H 13	305	305	80	2,45	150	100
HTF-13-A-305-610-80-S-DG-BG	H 13	305	610	80	4,90	300	100
HTF-13-A-457-457-80-S-DG-BG	H 13	457	457	80	5,50	340	100
HTF-13-A-535-535-80-S-DG-BG	H 13	535	535	80	7,55	465	100
HTF-13-A-575-575-80-S-DG-BG	H 13	575	575	80	8,70	535	100
HTF-13-A-610-610-80-S-DG-BG	H 13	610	610	80	9,80	600	100
HTF-13-A-610-762-80-S-DG-BG	H 13	610	762	80	12,25	750	100
HTF-13-A-610-915-80-S-DG-BG	H 13	610	915	80	14,70	900	100
HTF-13-A-610-1220-80-S-DG-BG	H 13	610	1220	80	19,60	1200	100
HTF-13-A-610-1830-80-S-DG-BG	H 13	610	1830	80	29,40	1800	100
HTF-14-A-203-203-80-S-DG-BG	H 14	203	203	80	1,10	75	125
HTF-14-A-305-305-80-S-DG-BG	H 14	305	305	80	2,45	150	125
HTF-14-A-305-610-80-S-DG-BG	H 14	305	610	80	4,90	300	125
HTF-14-A-457-457-80-S-DG-BG	H 14	457	457	80	5,50	340	125
HTF-14-A-535-535-80-S-DG-BG	H 14	535	535	80	7,55	465	125
HTF-14-A-575-575-80-S-DG-BG	H 14	575	575	80	8,70	535	125
HTF-14-A-610-610-80-S-DG-BG	H 14	610	610	80	9,80	600	125
HTF-14-A-610-762-80-S-DG-BG	H 14	610	762	80	12,25	750	125
HTF-14-A-610-915-80-S-DG-BG	H 14	610	915	80	14,70	900	125
HTF-14-A-610-1220-80-S-DG-BG	H 14	610	1220	80	19,60	1200	125
HTF-14-A-610-1830-80-S-DG-BG	H 14	610	1830	80	29,40	1800	125
HTF-15-A-203-203-80-S-DG-BG	U 15	203	203	80	1,10	75	145
HTF-15-A-305-305-80-S-DG-BG	U 15	305	305	80	2,45	150	145
HTF-15-A-305-610-80-S-DG-BG	U 15	305	610	80	4,90	300	145
HTF-15-A-457-457-80-S-DG-BG	U 15	457	457	80	5,50	340	145
HTF-15-A-535-535-80-S-DG-BG	U 15	535	535	80	7,55	465	145
HTF-15-A-575-575-80-S-DG-BG	U 15	575	575	80	8,70	535	145
HTF-15-A-610-610-80-S-DG-BG	U 15	610	610	80	9,80	600	145
HTF-15-A-610-762-80-S-DG-BG	U 15	610	762	80	12,25	750	145
HTF-15-A-610-915-80-S-DG-BG	U 15	610	915	80	14,70	900	145
HTF-15-A-610-1220-80-S-DG-BG	U 15	610	1220	80	19,60	1200	145
HTF-15-A-610-1830-80-S-DG-BG	U 15	610	1830	80	29,40	1800	145