

HEPA V COMPACT FILTERS



TECHNICAL SPECIFICATIONS

Filter Media : Minipleat Micro Glass Fibre
 Frame Material : Plastic Header Thickness 25mm
 Classification (EN1822) : E10 - U17
 Gasket : Cont. Round Pu / Flat Epdm
 Seperator : Hotmelt
 Sealant : 2K Polyur ethane
 Final Pressure Drop : 600 Pa
 Max. Temperature : 80 °C
 Max. Moisture : 90%



PRODUCT CODE	CLASS EN1822	WIDTH (mm)	HEIGHT (mm)	DEPTH (mm)	FILTRATION AREA (m2)	NOMINAL AIR FLOW (m3/h)	INITIAL PRESSURE DROP (± 10% Pa)
VC-10-287-592-CP	E 10	287	592	292	9,00	1700	170
VC-10-490-592-CP	E 10	490	592	292	15,00	2800	170
VC-10-592-592-CP	E 10	592	592	292	18,00	3400	170
VC-11-287-592-CP	E 11	287	592	292	9,00	1700	190
VC-11-490-592-CP	E 11	490	592	292	15,00	2800	190
VC-11-592-592-CP	E 11	592	592	292	18,00	3400	190
VC-12-287-592-CP	E 12	287	592	292	9,00	1700	210
VC-12-490-592-CP	E 12	490	592	292	15,00	2800	210
VC-12-592-592-CP	E 12	592	592	292	18,00	3400	210
VC-13-287-592-CP	H 13	287	592	292	9,00	1000	250
VC-13-490-592-CP	H 13	490	592	292	15,00	1650	250
VC-13-592-592-CP	H 13	592	592	292	18,00	2000	250

PRODUCT CODE EXPLANATION

