

HIGH FLOW FILTERS-292 MM ALUMINIUM FRAME

TECHNICAL SPECIFICATIONS

Filter Media	: Minipleat Micro Glass Fibre
Frame Material	: Aluminium Steel
Classification (EN1822)	: E10 - U17
Gasket	: Cont. Round Pu / Flat Epdm
Seperator	: Hotmelt
Sealant	: 2K Polyurethane
Final Pressure Drop	: 600 Pa
Max. Temperature	: 80 °C
Max. Moisture	: 90%



PRODUCT CODE	CLASS EN1822	WIDTH (mm)	HEIGHT (mm)	DEPTH (mm)	FILTRATION AREA (m2)	NOMINAL AIR FLOW (m3/h)	INITIAL PRESSURE DROP (± 10% Pa)
HFF-10-A-305-305-X-DP-DG	E 10	305	305	292	5,25	500	210
HFF-10-A-305-610-X-DP-DG	E 10	305	610	292	10,50	1000	210
HFF-10-A-610-610-X-DP-DG	E 10	610	610	292	21,00	2000	210
HFF-10-A-305-305-X-DP-DG	H 13	305	305	292	5,25	500	250
HFF-13-A-305-610-X-DP-DG	H 13	305	610	292	10,50	1000	250
HFF-13-A-610-610-X-DP-DG	H 13	610	610	292	21,00	2000	250
HFF-14-A-305-305-X-DP-DG	H 14	305	305	292	5,25	500	270
HFF-14-A-305-610-X-DP-DG	H 14	305	610	292	10,50	1000	270
HFF-14-A-610-610-X-DP-DG	H 14	610	610	292	21,00	2000	270
HFF-10-A-305-305-XL-DP-DG	E 10	305	305	292	6,75	750	210
HFF-10-A-305-610-XL-DP-DG	E 10	305	610	292	13,50	1500	210
HFF-10-A-610-610-XL-DP-DG	E 10	610	610	292	27,00	3000	210
HFF-10-A-305-305-XL-DP-DG	H 13	305	305	292	6,75	750	250
HFF-13-A-305-610-XL-DP-DG	H 13	305	610	292	13,50	1500	250
HFF-13-A-610-610-XL-DP-DG	H 13	610	610	292	27,00	3000	250
HFF-14-A-305-305-XL-DP-DG	H 14	305	305	292	6,75	750	270
HFF-14-A-305-610-XL-DP-DG	H 14	305	610	292	13,50	1500	270
HFF-14-A-610-610-XL-DP-DG	H 14	610	610	292	27,00	3000	270

