



TECHNICAL SPECIFICATIONS

Filter Media : Synthetic Polyester
 Frame Material : Galvanized Sheet Metal
 Frame Thickness : 20-25 mm
 Classification (EN779:2012) : M5-M6
 Classification (ISO 16890) : ePM10
 Final Pressure Drop : 450 Pa
 Max. Temperature : 80 °C
 Max. Moisture : 90%
 Rated Face Velocity : 2,70 m/s



PRODUCT CODE	CLASS EN779	CLASS ISO16890	WIDTH (mm)	HEIGHT (mm)	DEPTH (mm)	NUMBER OF POCKETS	FILTRATION AREA (m2)	NOMINAL AIR FLOW (m3/h)	INITIAL PRESSURE DROP (± 10 % Pa)
BF-5-25-287-592-360-3	M5	ePM10 55%	287	592	360	3	1,30	1700	90
BF-5-25-490-592-360-5	M5	ePM10 55%	490	592	360	5	2,10	2800	90
BF-5-25-592-592-360-6	M5	ePM10 55%	592	592	360	6	2,60	3400	90
BF-5-25-287-592-360-4	M5	ePM10 55%	287	592	360	4	1,70	1700	90
BF-5-25-490-592-360-6	M5	ePM10 55%	490	592	360	6	2,50	2800	90
BF-5-25-592-592-360-8	M5	ePM10 55%	592	592	360	8	3,40	3400	70
BF-5-25-287-592-535-3	M5	ePM10 55%	287	592	535	3	1,90	1700	70
BF-5-25-490-592-535-5	M5	ePM10 55%	490	592	535	5	3,20	2800	70
BF-5-25-592-592-535-6	M5	ePM10 55%	592	592	535	6	3,80	3400	70
BF-5-25-287-592-535-4	M5	ePM10 55%	287	592	535	4	2,50	1700	70
BF-5-25-490-592-535-6	M5	ePM10 55%	490	592	535	6	3,80	2800	65
BF-5-25-592-592-535-8	M5	ePM10 55%	592	592	535	8	5,00	3400	65
BF-5-25-287-592-635-3	M5	ePM10 55%	287	592	635	3	2,30	1700	65
BF-5-25-490-592-635-5	M5	ePM10 55%	490	592	635	5	3,80	2800	65
BF-5-25-592-592-635-6	M5	ePM10 55%	592	592	635	6	4,60	3400	65
BF-5-25-287-592-635-4	M5	ePM10 55%	287	592	635	4	3,00	1700	100
BF-5-25-490-592-635-6	M5	ePM10 70%	490	592	635	6	4,50	2800	100
BF-5-25-592-592-635-8	M5	ePM10 70%	592	592	635	8	6,00	3400	100
BF-6-25-287-592-360-3	M6	ePM10 70%	287	592	360	3	1,30	1700	100
BF-6-25-490-592-360-5	M6	ePM10 70%	490	592	360	5	2,10	2800	100
BF-6-25-592-592-360-6	M6	ePM10 70%	592	592	360	6	2,60	3400	100
BF-6-25-287-592-360-4	M6	ePM10 70%	287	592	360	4	1,70	1700	100
BF-6-25-490-592-360-6	M6	ePM10 70%	490	592	360	6	2,50	2800	100
BF-6-25-592-592-360-8	M6	ePM10 70%	592	592	360	8	3,40	3400	100
BF-6-25-287-592-535-3	M6	ePM10 70%	287	592	535	3	1,90	1700	100
BF-6-25-490-592-535-5	M6	ePM10 70%	490	592	535	5	3,20	2800	100
BF-6-25-592-592-535-6	M6	ePM10 70%	592	592	535	6	3,80	3400	80
BF-6-25-287-592-535-4	M6	ePM10 70%	287	592	535	4	2,50	1700	80
BF-6-25-490-592-535-6	M6	ePM10 70%	490	592	535	6	3,80	2800	80
BF-6-25-592-592-535-8	M6	ePM10 70%	592	592	535	8	5,00	3400	80
BF-6-25-287-592-635-3	M6	ePM10 70%	287	592	635	3	2,30	1700	80
BF-6-25-490-592-635-5	M6	ePM10 70%	490	592	635	5	3,80	2800	75
BF-6-25-592-592-635-6	M6	ePM10 70%	592	592	635	6	4,60	3400	75
BF-6-25-287-592-635-4	M6	ePM10 70%	287	592	635	4	3,00	1700	75
BF-6-25-490-592-635-6	M6	ePM10 70%	490	592	635	6	4,50	2800	75
BF-6-25-592-592-635-8	M6	ePM10 70%	592	592	635	8	6,00	3400	75